



**Luminaire**

# Lina60-S

04S-000K-15GGE/830, S


**EPD®**

You will appreciate the L-Click system on the Lina60-S luminaire with a direct light distribution, which effectively saves you both time and money. How? The module simply clicks into the profile, so a lot of work is saved during assembly. This solution also prevents the direct touch of the LED technology and lengthens its operating life. The Lina60-S lighting system can be assembled creating endless lines and a big variety of shapes. In addition to great power output, the luminaire also has a great price. It will find its use in commercial, social and public spaces.

**Technical drawing**


|  |                        |
|--|------------------------|
| Type of installation                   | Recessed               |
| Light distribution                     | Direct                 |
| Luminaire shape                        | Linear                 |
| Colour of the luminaires               | Silver                 |
| Material                               | Aluminium              |
| Lifetime                               | L90/B50 50 000 hours   |
| Warranty                               | 5 years                |
| Description of luminaires              | Luminaire recessed     |
| Dimensions                             | 842 mm × 76 mm × 67 mm |
| Weight                                 | 2.3 kg                 |
| Light source                           | LED MODUL              |
| Type of optical system                 | Opal diffuser          |
| Luminous flux*                         | 2330 lm                |
| Colour Temperature                     | 3000 K warm white      |
| Luminous efficacy                      | 125 lm/W               |
| MacAdam Light source                   | 2                      |
| Colour rendering index                 | 80                     |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 26.4                   |

## Curve



Luminaire power input\* 18.6 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

\*±10 %

## Downloads

Installation instructions



Photos



## Accessories



**00-00500**  
wire for emergency  
lighting XX-XXXX-20



**04-00100, S**  
2xend cap - metal, 3-  
conductor terminal box,  
grommet



**04-00200, N**  
straight connector



**04-01200, F**  
Accessory for gear-tray  
release