



## Luminaire

# Lina60-S


04S-200F-20GGE/940, S



EPD®

You will appreciate the L-Click system on the Lina60-S luminaire with a direct light distribution, which effectively saves you both time and money. How? The module simply clicks into the profile, so a lot of work is saved during assembly. This solution also prevents the direct touch of the LED technology and lengthens its operating life. The Lina60-S lighting system can be assembled creating endless lines and a big variety of shapes. In addition to great power output, the luminaire also has a great price. It will find its use in commercial, social and public spaces.

## Technical drawing



|  |   |
|--|---|
| Type of installation                   | Recessed, Surface, Wall mounted, Suspended        |
| Light distribution                     | Direct  |
| Luminaire shape                        | Linear  |
| Colour of the luminaires               | Silver  |
| Material                               | Aluminium   |
| Lifetime                               | L80/B20 50 000 hours                              |
| Warranty                               | 5 years   |
| Description of luminaires              | Luminaire recessed/surface/wall mounted/suspended |
| Dimensions (l × w × h mm)              | 561 mm × 57 mm × 67 mm                            |
| Light source                           | LED MODUL   |
| DIR optical system                     | Reflector   |
| Luminous flux*                         | 1750 lm   |
| Colour Temperature                     | 4000 K cool white                                 |
| Luminous efficacy                      | 88 lm/W   |
| MacAdam Light source                   | 3   |
| Colour rendering index                 | 90  |
| Beam angle                             | 45°   |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 22.8  |

## Curve



Luminaire power input\* 40 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**


**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm



**00-00302, N**  
wire suspension  
6000mm



**00-00350, K**  
cable 3x0,75 1000mm,  
transparent



**00-00352, K**  
cable 3x0,75 2000mm,  
transparent



**00-00358, K**  
cable 3x0,75 4000mm,  
transparent



**00-00360, K**  
cable 3x0,75 6000mm,  
transparent



**00-00370, S**  
ceiling cup 80x80x32mm



**00-00600, F**  
ceiling fastening for  
luminaires 132-5xxK,  
04-2000x, 05-2000x,  
09-200x - 1 piece



**00-20700, B**  
2 pcs of wall fastening  
Lipo/Lina



**04-00200, N**  
straight connector



**04-01200, F**  
Accessory for gear-tray  
release



**04-20100, S**  
2xend cap - metal, 3-  
conductor terminal box,  
grommet



**04-20102, S**  
2xend cap - plastic, 3-  
conductor terminal box,  
grommet



**04-20900, F**  
bracket for installation  
of suspended type of  
profile as recessed  
trimless