



## Luminaire

# Lina60-S

04S-200W-30GGE/930, S



EPD®

You will appreciate the L-Click system on the Lina60-S luminaire with a direct light distribution, which effectively saves you both time and money. How? The module simply clicks into the profile, so a lot of work is saved during assembly. This solution also prevents the direct touch of the LED technology and lengthens its operating life. The Lina60-S lighting system can be assembled creating endless lines and a big variety of shapes. In addition to great power output, the luminaire also has a great price. It will find its use in commercial, social and public spaces.

## Technical drawing



|                                   |   |
|-----------------------------------|---|
| Type of installation              | Recessed, Surface, Wall mounted, Suspended        |
| Light distribution                | Direct  |
| Luminaire shape                   | Linear  |
| Colour of the luminaires          | Silver  |
| Material                          | Aluminium   |
| Lifetime                          | L80/B20 50 000 hours                              |
| Warranty                          | 5 years   |
| Description of luminaires         | Luminaire recessed/surface/wall mounted/suspended |
| Dimensions (l × w × h mm)         | 561 mm × 57 mm × 67 mm                            |
| Light source                      | LED MODUL   |
| DIR optical system                | Reflector   |
| Luminous flux*                    | 1650 lm   |
| Colour Temperature                | 3000 K warm white                                 |
| Luminous efficacy                 | 83 lm/W   |
| MacAdam Light source              | 3   |
| Colour rendering index            | 90  |
| Beam angle                        | 68°   |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 24.3  |

## Curve



Luminaire power input\* 60 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**


**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm



**00-00302, N**  
wire suspension  
6000mm



**00-00350, K**  
cable 3x0,75 1000mm,  
transparent



**00-00352, K**  
cable 3x0,75 2000mm,  
transparent



**00-00358, K**  
cable 3x0,75 4000mm,  
transparent



**00-00360, K**  
cable 3x0,75 6000mm,  
transparent



**00-00370, S**  
ceiling cup 80x80x32mm



**00-00600, F**  
ceiling fastening for  
luminaires 132-5xxK,  
04-2000x, 05-2000x,  
09-200x - 1 piece



**00-20700, B**  
2 pcs of wall fastening  
Lipo/Lina



**04-00200, N**  
straight connector



**04-01200, F**  
Accessory for gear-tray  
release



**04-20100, S**  
2xend cap - metal, 3-  
conductor terminal box,  
grommet



**04-20102, S**  
2xend cap - plastic, 3-  
conductor terminal box,  
grommet



**04-20900, F**  
bracket for installation  
of suspended type of  
profile as recessed  
trimless