



Luminaire

Lina80-S


05S-020K-20GEE/830, S



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

Technical drawing



| | |
|--|-------------------------|
| Type of installation | Recessed |
| Light distribution | Direct |
| Luminaire shape | Corner |
| Colour of the luminaires | Silver |
| Material | Aluminium |
| Lifetime | L90/B50 50 000 hours |
| Warranty | 5 years |
| Description of luminaires | Luminaire recessed |
| Dimensions (l × w × h mm) | 622 mm × 622 mm × 84 mm |
| Weight | 5.2 kg |
| Light source | LED MODUL |
| DIR optical system | Opal diffuser |
| Luminous flux* | 2030 lm |
| Colour Temperature | 3000 K warm white |
| Luminous efficacy | 137 lm/W |
| MacAdam Light source | 2 |
| Colour rendering index | 80 |
| UGR max. X=4H Y=8H, $\rho=70,50,20$ | 20.8 |

| | |
|------------------------------|----------|
| Luminaire power input* | 14.8 W |
| Connection of the luminaires | ON/OFF |
| Electrical voltage | 220-240V |
| Frequency | 50/60Hz |

  IP 40

*±10 %

Downloads

Installation instructions



Photos

