



## Luminaire

# Lina80-S

05S-200B-20GHE/840, S



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

|                                   |  |
|-----------------------------------|--|
| Type of installation              | Surface, Wall mounted, Suspended         |
| Light distribution                | Direct                                   |
| Luminaire shape                   | Linear                                   |
| Colour of the luminaires          | Silver                                   |
| Material                          | Aluminium                                |
| Lifetime                          | L90/B50 50 000 hours                     |
| Warranty                          | 5 years                                  |
| Description of luminaires         | Luminaire surface/wall mounted/suspended |
| Dimensions                        | 1122 mm × 80 mm × 93 mm                  |
| Light source                      | LED MODUL                                |
| Type of optical system            | MP LOW UGR                               |
| Luminous flux*                    | 3370 lm                                  |
| Colour Temperature                | 4000 K cool white                        |
| Luminous efficacy                 | 123 lm/W                                 |
| MacAdam Light source              | 2  |
| Colour rendering index            | 80                                       |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 18.7                                     |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 27.3 W   |
| Connection of the luminaires | ON/OFF   |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

  IP 40

\*±10 %

## Downloads

Installation instructions



Photos

