


Luminaire

Lina80-S

05S-200I-40GEE/840, W


EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

Technical drawing


Type of installation	Recessed, Surface, Wall mounted, Suspended, 3 circuit track
Light distribution	Direct
Luminaire shape	Linear
Colour of the luminaires	White
Material	Aluminium
Lifetime	L90/B50 60 000 hours
Warranty	5 years
Description of luminaires	Luminaire recessed/surface/wall mounted/suspended/3 circuit track
Dimensions	2244 mm × 80 mm × 93 mm
Weight	9.6 kg
Light source	LED MODUL
Type of optical system	Microprisma
Luminous flux*	1890 lm
Colour Temperature	4000 K cool white
Luminous efficacy	121 lm/W
MacAdam Light source	2
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	16.8

Luminaire power input*	15.6 W
Connection of the luminaires	ON/OFF
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 40

*±10 %

Downloads

Installation instructions



Photos



Accessories

00-00200, N
straight connector

00-00300, N
wire suspension
2000mm

00-00301, N
wire suspension
4000mm

00-00302, N
wire suspension
6000mm

00-00350, K
cable 3x0,75 1000mm

00-00352, K
cable 3x0,75 2000mm

00-00358, K
cable 3x0,75 4000mm

00-00360, K
cable 3x0,75 6000mm

00-00363, K
cable 5x1,5 2000mm

00-00364, K
cable 5x1,5 4000mm

00-00365, K
cable 5x1,5 6000mm

00-00370, W
ceiling cup 80x80x32mm

00-00501
wire for emergency
lighting XX-XXXX-40

00-00600, F
ceiling fastening for
luminaires 132-5xxK,
04-2000x, 05-2000x,
09-200x - 1 piece

00-01200, F
Accessory for gear-tray
release

00-20100, W
2xend cap - metal, 3-
conductor terminal box,
grommet; Lipo80/Lina80

00-20102, W
2xend cap - plastic, 3-
conductor terminal box,
grommet; Lipo80/Lina80

00-20700, W
2 pcs of wall fastening
Lipo/Lina

00-20900, F
bracket for installation
of suspended type of
profile as recessed
trimless

00-21300, W
Lipo80-S, Lina80-S -
pendant profile for track
luminaires; l = 1122mm

00-21301, W
Lipo80-S, Lina80-S -
pendant profile for track
luminaires; l = 2242mm

00-51300, W
set for suspension into
3-phase track, non-
dimmable luminaires

00-51301, W
set for suspension into
3-phase track, dimmable
luminaires