



Luminaire

Lina80-S

05S-200K-60GETD/830, W




Type of installation	Recessed, Surface, Wall mounted, Suspended, 3 circuit track
Light distribution	Direct
Luminaire shape	Linear
Colour of the luminaires	White
Material	Aluminium
Lifetime	L90/B50 60 000 hours
Warranty	5 years
Description of luminaires	Luminaire recessed/surface/wall mounted/suspended/3 circuit track
Dimensions (l × w × h mm)	3366 mm × 80 mm × 93 mm
Light source	LED MODUL
DIR optical system	Opal diffuser
Luminous flux*	6100 lm
Colour Temperature	3000 K warm white
Luminous efficacy	137 lm/W
MacAdam Light source	2
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	23.4



Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

Technical drawing



Luminaire power input* 44.4 W

Connection of the luminaires Other type of dimming

Electrical voltage 220-240V

Frequency 50/60Hz

 **CE** IP 40

*±10 %

Downloads

Installation instructions



Photos



Accessories

00-00200, N
straight connector

00-00300, N
wire suspension
2000mm

00-00301, N
wire suspension
4000mm

00-00302, N
wire suspension
6000mm

00-00354, W
cable 5x0,75 1000mm,
white

00-00355, W
cable 5x0,75 2000mm,
white

00-00356, W
cable 5x0,75 4000mm,
white

00-00357, W
cable 5x0,75 6000mm,
white

00-00363, K
cable 5x1,5 2000mm

00-00364, K
cable 5x1,5 4000mm

00-00365, K
cable 5x1,5 6000mm

00-00366, K
cable 7x0,75 2000mm

00-00367, K
cable 7x0,75 4000mm

00-00368, K
cable 7x0,75 6000mm

00-00370, W
ceiling cup 80x80x32mm

00-00600, F
ceiling fastening for
luminaires 132-5xxK,
04-2000x, 05-2000x,
09-200x - 1 piece

00-01200, F
Accessory for gear-tray
release

00-20101, W
2xend cap - metal, 5-
conductor terminal box,
grommet; Lipo80/Lina80

00-20103, W
2xend cap - plastic, 5-
conductor terminal box,
grommet; Lipo80/Lina80

00-20700, W
2 pcs of wall fastening
Lipo/Lina

00-20900, F
bracket for installation
of suspended type of
profile as recessed
trimless

00-21300, W
Lipo80-S, Lina80-S -
pendant profile for track
luminaires; l = 1122mm

00-21301, W
Lipo80-S, Lina80-S -
pendant profile for track
luminaires; l = 2242mm

00-51300, W
set for suspension into
3-phase track, non-
dimmable luminaires

00-51301, W
set for suspension into
3-phase track, dimmable
luminaires