



## Luminaire


# Lina80-S

05S-230M-40GEE/840, W



Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

## Technical drawing



|                                   |   |
|-----------------------------------|---|
| Type of installation              | Recessed, Surface, Wall mounted, Suspended, 3 circuit track       |
| Light distribution                | Direct  |
| Luminaire shape                   | Linear  |
| Colour of the luminaires          | White   |
| Material                          | Aluminium   |
| Lifetime                          | L90/B50 50 000 hours  |
| Warranty                          | 5 years   |
| Description of luminaires         | Luminaire recessed/surface/wall mounted/suspended/3 circuit track |
| Dimensions (l × w × h mm)         | 2249 mm × 80 mm × 93 mm   |
| Light source                      | LED MODUL   |
| DIR optical system                | Matt parabolic louvre   |
| Luminous flux*                    | 5830 lm   |
| Colour Temperature                | 4000 K cool white   |
| Luminous efficacy                 | 118 lm/W  |
| MacAdam Light source              | 2   |
| Colour rendering index            | 80  |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 16.3  |

## Curve



Luminaire power input\* 49.2 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos

