



## Luminaire

# Lina80

11-531M-30GED/830, W



Type of installation	Suspended
Light distribution	Direct-indirect
Luminaire shape	Linear
Colour of the luminaires	White
Material	Aluminium
Lifetime	L90/B50 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
item description	White ceiling cup and cable

Dimensions  
(l × w × h mm) 1688 mm × 80 mm × 93 mm

DIR optical system Matt parabolic louvre

INDIR optical system Opal cover

Luminous flux\* 2720 lm

Colour Temperature 3000 K warm white

Luminous efficacy 49 lm/W

MacAdam Light source 2


Colour rendering index 80

UGR max. X=4H 16.2  
Y=8H, ρ=70,50,20




Lina80 luminaires with an easy L-Click system feature an elegant and classic linear design with excellent illumination characteristics with both ceiling mounted and suspended versions, allowing them to fit into almost any space. Lina80 lighting is the right solution for offices, business, social and cultural spaces, as well as households and restaurants. With Tunable White, you set the white color temperature according to the time of day. The light thus provides optimal light helping you to focus on and concentrate on the work.

## Technical drawing



## Curve



Luminaire power input\* 55.6 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE  IP 20

\*±10 %

## Downloads

Installation instructions



Photos

