



## Luminaire

# Lina80-S

11S-501B-15GHD/830, S



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

## Technical drawing



Type of installation Wall mounted, Suspended

Light distribution Direct-indirect

Luminaire shape Linear

Colour of the luminaires Silver

Material Aluminium

Lifetime L90/B50 50 000 hours

Warranty 5 years

Description of luminaires Luminaire wall mounted/suspended

Dimensions (l × w × h mm) 842 mm × 80 mm × 93 mm

Light source LED MODUL

DIR optical system MP LOW UGR

INDIR optical system Opal cover

Luminous flux\* 3690 lm

Colour Temperature 3000 K warm white

Luminous efficacy 127 lm/W

MacAdam Light source 2

Colour rendering index 80

## Curve



Luminaire power input\* 29 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

\* $\pm 10\%$

## Downloads

Installation instructions



Photos

