



## Luminaire

# Lina80-S

11S-501B-40GHE/830, S



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

## Technical drawing



Type of installation Wall mounted, Suspended

Light distribution Direct-indirect

Luminaire shape Linear

Colour of the luminaires Silver

Material Aluminium

Lifetime L90/B50 50 000 hours

Warranty 5 years

Description of luminaires Luminaire wall mounted/suspended

Dimensions 2244 mm × 80 mm × 93 mm  
(l × w × h mm)

Light source LED MODUL

DIR optical system MP LOW UGR

INDIR optical system Opal cover

Luminous flux\* 11530 lm

Colour Temperature 3000 K warm white


Luminous efficacy 119 lm/W

MacAdam Light source 2

Colour rendering index 80

UGR max. X=4H 15.2  
Y=8H, ρ=70,50,20

## Curve



Luminaire power input\* 97.2 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

\*±10 %

## Downloads

Installation instructions



Photos

