



## Luminaire

# Lina80-S

11S-501I-25GEE/840, B



EPD®

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

## Technical drawing



Type of installation Wall mounted, Suspended

Light distribution Direct-indirect

Luminaire shape Linear

Colour of the luminaires Black

Material Aluminium

Lifetime L90/B50 50 000 hours

Warranty 5 years

Description of luminaires Luminaire wall mounted/suspended

Dimensions 1403 mm × 80 mm × 93 mm  
(l × w × h mm)

Weight 5.4 kg

Light source LED MODUL

DIR optical system Microprisma

INDIR optical system Opal cover

Luminous flux\* 3630 lm

Colour Temperature 4000 K cool white

Luminous efficacy 121 lm/W

MacAdam Light source 2

Colour rendering index 80

UGR max. X=4H 16  
Y=8H,  $\theta=70,50,20$

## Curve



Luminaire power input\* 30.1 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**

**00-00200, N**  
 straight connector

**00-00300, N**  
 wire suspension  
 2000mm

**00-00301, N**  
 wire suspension  
 4000mm

**00-00302, N**  
 wire suspension  
 6000mm

**00-00352, B**  
 cable 3x0,75 2000mm,  
 black

**00-00355, B**  
 cable 5x0,75 2000mm,  
 black

**00-00356, B**  
 cable 5x0,75 4000mm,  
 black

**00-00358, B**  
 cable 3x0,75 4000mm,  
 black

**00-00360, B**  
 cable 3x0,75 6000mm,  
 black

**00-00363, K**  
 cable 5x1,5 2000mm

**00-00364, K**  
 cable 5x1,5 4000mm

**00-00365, K**  
 cable 5x1,5 6000mm

**00-00370, B**  
 ceiling cup 80x80x32mm

**00-01200, F**  
 Accessory for gear-tray  
 release

**00-20101, B**  
 2xend cap - metal, 5-  
 conductor terminal box,  
 grommet; Lipo80/Lina80

**00-20103, B**  
 2xend cap - plastic, 5-  
 conductor terminal box,  
 grommet; Lipo80/Lina80

**00-20700, B**  
 2 pcs of wall fastening  
 Lipo/Lina

**00-51300, B**  
 set for suspension into  
 3-phase track, non-  
 dimmable luminaires