



## Luminaire

# Lina80-S

11S-501I-35GGM3/840, B



Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

## Technical drawing



Type of installation Wall mounted, Suspended

Light distribution Direct-indirect

Luminaire shape Linear

Colour of the luminaires Black

Material Aluminium

Lifetime L90/B50 50 000 hours

Warranty 2 years

Description of luminaires Luminaire wall mounted/suspended

Dimensions (l × w × h mm) 1964 mm × 80 mm × 93 mm

Light source LED MODUL

DIR optical system Microprisma

INDIR optical system Opal cover

Luminous flux\* 8390 lm

Colour Temperature 4000 K cool white

Luminous efficacy 114 lm/W

MacAdam Light source 2

Colour rendering index 80

UGR max. X=4H Y=8H, ρ=70,50,20 17.2

## Curve



Luminaire power input\* 73.8 W

Connection of the luminaires ON/OFF + 3h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**


**00-00200, N**  
straight connector



**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm



**00-00302, N**  
wire suspension  
6000mm



**00-00355, B**  
cable 5x0,75 2000mm,  
black



**00-00356, B**  
cable 5x0,75 4000mm,  
black



**00-00363, K**  
cable 5x1,5 2000mm



**00-00364, K**  
cable 5x1,5 4000mm



**00-00365, K**  
cable 5x1,5 6000mm



**00-00366, K**  
cable 7x0,75 2000mm



**00-00367, K**  
cable 7x0,75 4000mm



**00-00368, K**  
cable 7x0,75 6000mm



**00-00370, B**  
ceiling cup 80x80x32mm



**00-01200, F**  
Accessory for gear-tray  
release



**00-20101, B**  
2xend cap - metal, 5-  
conductor terminal box,  
grommet; Lipo80/Lina80



**00-20103, B**  
2xend cap - plastic, 5-  
conductor terminal box,  
grommet; Lipo80/Lina80



**00-20700, B**  
2 pcs of wall fastening  
Lipo/Lina/Sant



**00-51300, B**  
set for suspension into  
3-phase track, non-  
dimmable luminaires