


**Luminaire**

# Lina80-S

11S-531M-30GED/840, B


**EPD®**

Lina80-S luminaires are available in recessed, surface, suspended or wall mounted versions, including the illuminated corner segments. Lina80-S system luminaire can be used to create different shapes or long lines, with special joints that prevent any light to shine through, creating thus a seamless visual effect, suitable for small offices as well as big halls.

**Technical drawing**


Type of installation	Suspended
Light distribution	Direct-indirect
Luminaire shape	Linear
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L90/B50 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
Dimensions (l × w × h mm)	1688 mm × 80 mm × 93 mm
DIR optical system	Matt parabolic louvre
INDIR optical system	Opal cover
Luminous flux*	6759 lm
Colour Temperature	4000 K cool white
Luminous efficacy	122 lm/W
MacAdam Light source	2
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	16.3

## Curve



Luminaire power input\* 55.6 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**


**00-00200, N**  
straight connector



**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm



**00-00302, N**  
wire suspension  
6000mm



**00-00355, B**  
cable 5x0,75 2000mm,  
black



**00-00356, B**  
cable 5x0,75 4000mm,  
black



**00-00357, B**  
cable 5x0,75 6000mm,  
black



**00-00363, K**  
cable 5x1,5 2000mm



**00-00364, K**  
cable 5x1,5 4000mm



**00-00365, K**  
cable 5x1,5 6000mm



**00-00370, B**  
ceiling cup 80x80x32mm



**00-01200, F**  
Accessory for gear-tray  
release



**00-20101, B**  
2xend cap - metal, 5-  
conductor terminal box,  
grommet; Lipo80/Lina80



**00-20103, B**  
2xend cap - plastic, 5-  
conductor terminal box,  
grommet; Lipo80/Lina80



**00-20700, B**  
2 pcs of wall fastening  
Lipo/Lina



**00-51300, B**  
set for suspension into  
3-phase track, non-  
dimmable luminaires