



Luminaire


Zuli

121-200K-40GED/840, B



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

Technical drawing



| | |
|---------------------------|-----------------------------|
| Type of installation | Surface, Suspended |
| Light distribution | Direct |
| Colour of the luminaires | Black |
| Material | Aluminium |
| Lifetime | L80/B20 50 000 hours |
| Warranty | 5 years |
| Description of luminaires | Luminaire surface/suspended |

| | |
|--------------|--------------------------|
| Dimensions | 2265 mm × 125 mm × 50 mm |
| Light source | LED MODUL |

| | |
|------------------------|---------------|
| Type of optical system | Opal diffuser |
|------------------------|---------------|

| | |
|----------------|---------|
| Luminous flux* | 6280 lm |
|----------------|---------|

| | |
|--------------------|-------------------|
| Colour Temperature | 4000 K cool white |
|--------------------|-------------------|

| | |
|-------------------|----------|
| Luminous efficacy | 147 lm/W |
|-------------------|----------|

| | |
|----------------------|---|
| MacAdam Light source | 2 |
|----------------------|---|

| | |
|------------------------|----|
| Colour rendering index | 80 |
|------------------------|----|

| | |
|------------------------|--------|
| Luminaire power input* | 42.8 W |
|------------------------|--------|

| | |
|------------------------------|------|
| Connection of the luminaires | DALI |
|------------------------------|------|

| | |
|--------------------|----------|
| Electrical voltage | 220-240V |
|--------------------|----------|

| | |
|-----------|---------|
| Frequency | 50/60Hz |
|-----------|---------|

  IP 20

*±10 %

Downloads

Installation instructions



Photos

