



## Luminaire

# Zuli

121-301K-10GEM3/840, S



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

## Technical drawing



|  |                         |
|--|-------------------------|
| Type of installation                   | Wall mounted            |
| Light distribution                     | Direct-indirect         |
| Luminaire shape                        | Angular                 |
| Colour of the luminaires               | Silver                  |
| Material                               | Aluminium               |
| Lifetime                               | L80/B10 50 000 hours    |
| Warranty                               | 2 years                 |
| Description of luminaires              | Luminaire wall mounted  |
| Dimensions<br>(l × w × h mm)           | 590 mm × 125 mm × 50 mm |
| Weight                                 | 1.9 kg                  |
| Light source                           | LED MODUL               |
| DIR optical system                     | Opal diffuser           |
| INDIR optical system                   | Celar cover             |
| Luminous flux*                         | 2120 lm                 |
| Colour Temperature                     | 4000 K cool white       |
| Luminous efficacy                      | 131 lm/W                |
| MacAdam Light source                   | 2                       |
| Colour rendering index                 | 80                      |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 18.1                    |

|                              |                       |
|------------------------------|-----------------------|
| Luminaire power input*       | 16.2 W                |
| Connection of the luminaires | ON/OFF + 3h emergency |
| Electrical voltage           | 220-240V              |
| Frequency                    | 50/60Hz               |

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos

