



Luminaire

Zuli

121-301K-15GHD/830, W



Do you remember the buzzing and flickering lights of your classroom? Fortunately these are long gone. Zuli pendant and surface-mounted LED luminaires ensure comfortable lighting in the classroom, offices and hospitals without these annoyances. These luminaires have direct or direct-indirect emission, with a choice of four lengths and microprism optics, grid and opal diffuser.

Technical drawing



| | |
|--|-------------------------|
| Type of installation | Wall mounted |
| Light distribution | Direct-indirect |
| Luminaire shape | Angular |
| Colour of the luminaires | White |
| Material | Aluminium |
| Lifetime | L80/B20 50 000 hours |
| Warranty | 5 years |
| Description of luminaires | Luminaire wall mounted |
| Dimensions (l × w × h mm) | 865 mm × 125 mm × 50 mm |
| Weight | 2.44 kg |
| Light source | LED MODUL |
| DIR optical system | Opal diffuser |
| INDIR optical system | Celar cover |
| Luminous flux* | 6850 lm |
| Colour Temperature | 3000 K warm white |
| Luminous efficacy | 112 lm/W |
| MacAdam Light source | 2 |
| Colour rendering index | 80 |
| UGR max. X=4H Y=8H, $\theta=70,50,20$ | 20.9 |

Luminaire power input* 60.9 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

  IP 20

*±10 %

Downloads

Installation instructions



Photos

