



## Luminaire

# Zuli-S

121S-200I-40GED/830, S



We realize that there is beauty in simplicity, so we have created our Zuli-S system luminaire. The Zuli-S luminaire is based on the timeless shape that everyone has known for many years. The luminaires come with a very efficient LED light source, thanks to which the luminaires have a very high economical and, last but not least, ecological value, as they require a relatively small amount of energy. Zuli-S luminaires can be fitted with a parabolic louver made of polished aluminium sheet or an opal diffuser.

## Technical drawing



|                           |                             |
|---------------------------|-----------------------------|
| Type of installation      | Surface, Suspended          |
| Light distribution        | Direct                      |
| Colour of the luminaires  | Silver                      |
| Material                  | Aluminium                   |
| Lifetime                  | L80/B20 50 000 hours        |
| Warranty                  | 5 years                     |
| Description of luminaires | Luminaire surface/suspended |

|              |                          |
|--------------|--------------------------|
| Dimensions   | 2255 mm × 125 mm × 50 mm |
| Light source | LED MODUL                |

|                        |             |
|------------------------|-------------|
| Type of optical system | Microprisma |
|------------------------|-------------|

|                |         |
|----------------|---------|
| Luminous flux* | 3510 lm |
|----------------|---------|

|                    |                   |
|--------------------|-------------------|
| Colour Temperature | 3000 K warm white |
|--------------------|-------------------|

|                   |          |
|-------------------|----------|
| Luminous efficacy | 121 lm/W |
|-------------------|----------|

|                      |   |
|----------------------|---|
| MacAdam Light source | 2 |
|----------------------|---|

|                        |    |
|------------------------|----|
| Colour rendering index | 80 |
|------------------------|----|

|                                   |      |
|-----------------------------------|------|
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 17.2 |
|-----------------------------------|------|

|                        |        |
|------------------------|--------|
| Luminaire power input* | 29.1 W |
|------------------------|--------|

|                              |      |
|------------------------------|------|
| Connection of the luminaires | DALI |
|------------------------------|------|

|                    |          |
|--------------------|----------|
| Electrical voltage | 220-240V |
|--------------------|----------|

|           |         |
|-----------|---------|
| Frequency | 50/60Hz |
|-----------|---------|

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**

**00-00352, K**  
 cable 3x0,75 2000mm

**00-00355, K**  
 cable 5x0,75 2000mm

**00-00356, K**  
 cable 5x0,75 4000mm

**00-00358, K**  
 cable 3x0,75 4000mm

**00-00360, K**  
 cable 3x0,75 6000mm

**00-00363, K**  
 cable 5x1,5 2000mm

**00-00364, K**  
 cable 5x1,5 4000mm

**00-00365, K**  
 cable 5x1,5 6000mm

**00-00370, S**  
 ceiling cup 80x80x32mm

**121-00200, N**  
 straight connector

**121-00300, N**  
 wire suspension  
 2000mm

**121-00301, N**  
 wire suspension  
 4000mm

**121-00302, N**  
 wire suspension  
 6000mm

**121-20101, S**  
 2xend cap - plastic