



## Luminaire

# Zuli-S

121S-500K-20GGE/840, S



We realize that there is beauty in simplicity, so we have created our Zuli-S system luminaire. The Zuli-S luminaire is based on the timeless shape that everyone has known for many years. The luminaires come with a very efficient LED light source, thanks to which the luminaires have a very high economical and, last but not least, ecological value, as they require a relatively small amount of energy. Zuli-S luminaires can be fitted with a parabolic louver made of polished aluminium sheet or an opal diffuser.

## Technical drawing



|                           |                          |
|---------------------------|--------------------------|
| Type of installation      | Suspended                |
| Light distribution        | Direct                   |
| Luminaire shape           | Linear                   |
| Colour of the luminaires  | Silver                   |
| Material                  | Aluminium                |
| Lifetime                  | L80/B20 50 000 hours     |
| Warranty                  | 5 years                  |
| Description of luminaires | Luminaire suspended      |
| Dimensions (l × w × h mm) | 1135 mm × 125 mm × 50 mm |
| Weight                    | 3.1 kg                   |
| Light source              | LED MODUL                |
| DIR optical system        | Opal diffuser            |
| Luminous flux*            | 4310 lm                  |
| Colour Temperature        | 4000 K cool white        |
| Luminous efficacy         | 139 lm/W                 |
| MacAdam Light source      | 2                        |
| Colour rendering index    | 80                       |

## Curve



Luminaire power input\* 31.1 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**


**00-00352, K**  
cable 3x0,75 2000mm,  
transparent



**00-00355, K**  
cable 5x0,75 2000mm,  
transparent



**00-00356, K**  
cable 5x0,75 4000mm,  
transparent



**00-00358, K**  
cable 3x0,75 4000mm,  
transparent



**00-00360, K**  
cable 3x0,75 6000mm,  
transparent



**00-00363, K**  
cable 5x1,5 2000mm



**00-00364, K**  
cable 5x1,5 4000mm



**00-00365, K**  
cable 5x1,5 6000mm



**00-00370, S**  
ceiling cup 80x80x32mm



**121-00200, N**  
straight connector




**121-00300, N**  
wire suspension  
2000mm



**121-00301, N**  
wire suspension  
4000mm



**121-00302, N**  
wire suspension  
6000mm



**121-20101, S**  
2xend cap - plastic