



Luminaire


Zuli-S

121S-501K-40GEE/840, W



We realize that there is beauty in simplicity, so we have created our Zuli-S system luminaire. The Zuli-S luminaire is based on the timeless shape that everyone has known for many years. The luminaires come with a very efficient LED light source, thanks to which the luminaires have a very high economical and, last but not least, ecological value, as they require a relatively small amount of energy. Zuli-S luminaires can be fitted with a parabolic louver made of polished aluminium sheet or an opal diffuser.

Technical drawing



Type of installation	Suspended
Light distribution	Direct-indirect
Colour of the luminaires	White
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
Dimensions	2255 mm × 125 mm × 50 mm
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux*	10470 lm
Colour Temperature	4000 K cool white
Luminous efficacy	140 lm/W
MacAdam Light source	2
Colour rendering index	80
Luminaire power input*	74.9 W
Connection of the luminaires	ON/OFF
Electrical voltage	220-240V
Frequency	50/60Hz

*±10 %

Downloads

Installation instructions



Photos



Accessories

00-00352, K
cable 3x0,75 2000mm

00-00355, K
cable 5x0,75 2000mm

00-00356, K
cable 5x0,75 4000mm

00-00358, K
cable 3x0,75 4000mm

00-00360, K
cable 3x0,75 6000mm

00-00363, K
cable 5x1,5 2000mm

00-00364, K
cable 5x1,5 4000mm


00-00365, K
cable 5x1,5 6000mm

00-00370, S
ceiling cup 80x80x32mm

121-00200, N
straight connector

121-00300, N
wire suspension
2000mm

121-00301, N
wire suspension
4000mm

121-00302, N
wire suspension
6000mm

121-20101, W
2xend cap - plastic