


**Luminaire**

# Rotao100

127-561K-10GEE/840, W



|  |                      |
|--|----------------------|
| Type of installation                   | Suspended            |
| Light distribution                     | Direct-indirect      |
| Luminaire shape                        | Circular             |
| Colour of the luminaires               | White                |
| Material                               | Aluminium            |
| Lifetime                               | L80/B20 50 000 hours |
| Warranty                               | 5 years              |
| Description of luminaires              | Luminaire suspended  |
| Dimensions                             | ø 600 mm × 87 mm     |
| Weight                                 | 6.1 kg               |
| Light source                           | LED MODUL            |
| Type of optical system                 | Opal diffuser        |
| Luminous flux*                         | 3160 lm              |
| Colour Temperature                     | 4000 K cool white    |
| Luminous efficacy                      | 114 lm/W             |
| MacAdam Light source                   | 3                    |
| Colour rendering index                 | 80                   |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 21.2                 |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 27.7 W   |
| Connection of the luminaires | ON/OFF   |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

 **CE** IP 20

\*±10 %

## Downloads

Installation instructions



Photos

