


**Luminaire**

# Rotao100

127-580I-10GEE/840, B


**Technical drawing**


|  |                      |
|--|----------------------|
| Type of installation                   | Suspended            |
| Light distribution                     | Direct               |
| Luminaire shape                        | Circular             |
| Colour of the luminaires               | Black                |
| Material                               | Aluminium            |
| Lifetime                               | L80/B20 50 000 hours |
| Warranty                               | 5 years              |
| Description of luminaires              | Luminaire suspended  |
| Dimensions                             | ø 850 mm × 87 mm     |
| Weight                                 | 8.5 kg               |
| Light source                           | LED MODUL            |
| Type of optical system                 | Microprisma          |
| Luminous flux*                         | 3220 lm              |
| Colour Temperature                     | 4000 K cool white    |
| Luminous efficacy                      | 92 lm/W              |
| MacAdam Light source                   | 3                    |
| Colour rendering index                 | 80                   |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 17.8                 |

## Curve



Luminaire power input\* 34.9 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos

