


**Luminaire**

# Rotao100

127-580K-10GED/830, B


**Technical drawing**


|                                   |                             |
|-----------------------------------|-----------------------------|
| Type of installation              | Suspended                   |
| Light distribution                | Direct                      |
| Luminaire shape                   | Circular                    |
| Colour of the luminaires          | Black                       |
| Material                          | Aluminium                   |
| Lifetime                          | L80/B20 50 000 hours        |
| Warranty                          | 5 years                     |
| Description of luminaires         | Luminaire suspended         |
| item description                  | Black ceiling cup and cable |
| Dimensions                        | ø 850 mm × 87 mm            |
| Weight                            | 8.7 kg                      |
| Light source                      | LED MODUL                   |
| DIR optical system                | Opal diffuser               |
| Luminous flux*                    | 3800 lm                     |
| Colour Temperature                | 3000 K warm white           |
| Luminous efficacy                 | 109 lm/W                    |
| MacAdam Light source              | 3                           |
| Colour rendering index            | 80                          |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 22.6                        |

## Curve



Luminaire power input\* 34.9 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos

