


**Luminaire**

# Rotao100

127-581I-10GEE/830, W


**Technical drawing**


|                                   |                             |
|-----------------------------------|-----------------------------|
| Type of installation              | Suspended                   |
| Light distribution                | Direct-indirect             |
| Luminaire shape                   | Circular                    |
| Colour of the luminaires          | White                       |
| Material                          | Aluminium                   |
| Lifetime                          | L80/B20 50 000 hours        |
| Warranty                          | 5 years                     |
| Description of luminaires         | Luminaire suspended         |
| item description                  | White ceiling cup and cable |
| Dimensions                        | ø 850 mm × 87 mm            |
| Weight                            | 9.2 kg                      |
| Light source                      | LED MODUL                   |
| DIR optical system                | Microprisma                 |
| INDIR optical system              | Opal cover                  |
| Luminous flux*                    | 3680 lm                     |
| Colour Temperature                | 3000 K warm white           |
| Luminous efficacy                 | 89 lm/W                     |
| MacAdam Light source              | 3                           |
| Colour rendering index            | 80                          |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 16.4                        |

## Curve



Luminaire power input\* 41.5 W

Connection of the luminaires ON/OFF

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\*±10 %

## Downloads

Installation instructions



Photos

