


**Luminaire**

# Rotao100

127-5C1I-10GED/840, S


**Technical drawing**


|                                   |  |
|-----------------------------------|--|
| Type of installation              | Suspended                                |
| Light distribution                | Direct-indirect                          |
| Luminaire shape                   | Circular                                 |
| Colour of the luminaires          | Silver                                   |
| Material                          | Aluminium                                |
| Lifetime                          | L80/B20 50 000 hours                     |
| Warranty                          | 5 years                                  |
| Description of luminaires         | Luminaire suspended                      |
| item description                  | Silver ceiling cup and transparent cable |
| Dimensions                        | ø 1500 mm × 87 mm                        |
| Weight                            | 19.5 kg                                  |
| Light source                      | LED MODUL                                |
| DIR optical system                | Microprisma                              |
| INDIR optical system              | Opal cover                               |
| Luminous flux*                    | 6510 lm                                  |
| Colour Temperature                | 4000 K cool white                        |
| Luminous efficacy                 | 93 lm/W                                  |
| MacAdam Light source              | 3  |
| Colour rendering index            | 80                                       |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 16.7                                     |

## Curve



Luminaire power input\* 69.9 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

\* $\pm 10\%$

## Downloads

Installation instructions



Photos

