


**Luminaire**

# Rotao100

127-5D1K-10GEE/840, W


**Curve**


|                                   |                      |
|-----------------------------------|----------------------|
| Type of installation              | Suspended            |
| Light distribution                | Direct-indirect      |
| Luminaire shape                   | Circular             |
| Colour of the luminaires          | White                |
| Material                          | Aluminium            |
| Lifetime                          | L80/B20 50 000 hours |
| Warranty                          | 5 years              |
| Description of luminaires         | Luminaire suspended  |
| Dimensions                        | ∅ 2000 mm × 87 mm    |
| Weight                            | 26 kg                |
| Light source                      | LED MODUL            |
| Type of optical system            | Opal diffuser        |
| Luminous flux*                    | 12330 lm             |
| Colour Temperature                | 4000 K cool white    |
| Luminous efficacy                 | 114 lm/W             |
| MacAdam Light source              | 3                    |
| Colour rendering index            | 80                   |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 21                   |

Luminaire power input\* 107.7 W

---

Connection of the luminaires ON/OFF

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos

