


**Luminaire**

# Flumo100-S

**128S-500K-10GGD/830, S**


Large spaces and long corridors – such places require something special: a linear aluminium profile that winds along the corridor in a perfect curve and navigates you through the space. The system luminaires of the Flumo100-S family will fully adapt to your possibilities and imagination. They can run straight or meander like the Colorado River. All the different lengths and angles mean that there are no limits. To assemble the Flumo100-S lighting system you can choose between the pendant and surface versions. They are available with an opal diffuser or microprism in a wide range of colours according to the Halla RAL chart. The luminaires can be controlled via Bluetooth technology from your smart device.

Type of installation	Suspended
Light distribution	Direct
Luminaire shape	Linear
Colour of the luminaires	Silver
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
Dimensions (l × w × h mm)	580 mm × 100 mm × 87 mm
Light source	LED MODUL
DIR optical system	Opal diffuser
Luminous flux*	1110 lm
Colour Temperature	3000 K warm white
Luminous efficacy	101 lm/W
MacAdam Light source	3
Colour rendering index	80
Luminaire power input*	11 W
Connection of the luminaires	DALI
Electrical voltage	220-240V
Frequency	50/60Hz

 **IP 20**

\*±10 %

## Technical drawing



## Curve



## Downloads

Installation instructions



Photos

