


Luminaire

Flumo100-S

128S-500K-40GGD/830, S


Large spaces and long corridors – such places require something special: a linear aluminium profile that winds along the corridor in a perfect curve and navigates you through the space. The system luminaires of the Flumo100-S family will fully adapt to your possibilities and imagination. They can run straight or meander like the Colorado River. All the different lengths and angles mean that there are no limits. To assemble the Flumo100-S lighting system you can choose between the pendant and surface versions. They are available with an opal diffuser or microprism in a wide range of colours according to the Halla RAL chart. The luminaires can be controlled via Bluetooth technology from your smart device.

Type of installation	Suspended
Light distribution	Direct
Luminaire shape	Linear
Colour of the luminaires	Silver
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
Dimensions (l × w × h mm)	2260 mm × 100 mm × 87 mm
Weight	8.9 kg
Light source	LED MODUL
DIR optical system	Opal diffuser
Luminous flux*	4440 lm
Colour Temperature	3000 K warm white
Luminous efficacy	101 lm/W
MacAdam Light source	3
Colour rendering index	80

Technical drawing



Luminaire power input* 43.9 W

Connection of the luminaires DALI

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 20

*±10 %

Curve



Downloads

Installation instructions



Photos



Accessories**00-00300, N**
wire suspension
2000mm**00-00301, N**
wire suspension
4000mm**00-00302, N**
wire suspension
6000mm**00-00355, K**
cable 5x0,75 2000mm,
transparent**00-00356, K**
cable 5x0,75 4000mm,
transparent**00-00357, K**
cable 5x0,75 6000mm,
transparent**00-00370, S**
ceiling cup 80x80x32mm**128-20101, S**
2xend cap**128-20200, N**
arranging coupler