



## Luminaire

# Flumo100-S

128S-5C0I-045GE/840, S



Large spaces and long corridors – such places require something special: a linear aluminium profile that winds along the corridor in a perfect curve and navigates you through the space. The system luminaires of the Flumo100-S family will fully adapt to your possibilities and imagination. They can run straight or meander like the Colorado River. All the different lengths and angles mean that there are no limits. To assemble the Flumo100-S lighting system you can choose between the pendant and surface versions. They are available with an opal diffuser or microprism in a wide range of colours according to the Halla RAL chart. The luminaires can be controlled via Bluetooth technology from your smart device.

Type of installation    Suspended

Light distribution    Direct

Luminaire shape    Rounded

Colour of the luminaires    Silver

Material    Aluminium

Lifetime    L80/B20 50 000 hours

Warranty    5 years

Description of luminaires    Luminaire suspended

item description    R750 - 45°

Dimensions (w × h mm)    100 mm × 87 mm

Diameter    ø 750

Angle    45 °

Light source    LED MODUL

DIR optical system    Microprisma

Luminous flux\*    910 lm


Colour Temperature    4000 K cool white

Luminous efficacy    83 lm/W

MacAdam Light source    3

Colour rendering index    80


Technical drawing



|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 10.9 W   |
| Connection of the luminaires | ON/OFF   |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

⊕ **CE** IP 20  
\*±10 %

Curve



## Downloads

[Installation instructions](#)[Photos](#)

## Accessories



**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm




**00-00302, N**  
wire suspension  
6000mm



**00-00352, K**  
cable 3x0,75 2000mm,  
transparent



**00-00358, K**  
cable 3x0,75 4000mm,  
transparent



**00-00360, K**  
cable 3x0,75 6000mm,  
transparent



**00-00370, S**  
ceiling cup 80x80x32mm



**128-20101, S**  
2xend cap



**128-20200, N**  
arranging coupler