



Luminaire

Flumo100-S

128S-5E0I-060EE/840, B



Large spaces and long corridors – such places require something special: a linear aluminium profile that winds along the corridor in a perfect curve and navigates you through the space. The system luminaires of the Flumo100-S family will fully adapt to your possibilities and imagination. They can run straight or meander like the Colorado River. All the different lengths and angles mean that there are no limits. To assemble the Flumo100-S lighting system you can choose between the pendant and surface versions. They are available with an opal diffuser or microprism in a wide range of colours according to the Halla RAL chart. The luminaires can be controlled via Bluetooth technology from your smart device.

Type of installation Suspended

Light distribution Direct

Luminaire shape Rounded

Colour of the luminaires Black

Material Aluminium

Lifetime L80/B20 50 000 hours

Warranty 5 years

Description of luminaires Luminaire suspended

item description R1250 - 60°

Dimensions (w × h mm) 100 mm × 87 mm

Diameter ø 1250

Angle 60 °

Weight 4.9 kg

Light source LED MODUL

DIR optical system Microprisma

Luminous flux* 1610 lm

Colour Temperature 4000 K cool white

Luminous efficacy 87 lm/W

MacAdam Light source 3

Colour rendering index 80

Technical drawing



Luminaire power input*	18.5 W
Connection of the luminaires	ON/OFF
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 20
*±10 %

Curve



Downloads

[Installation instructions](#)[Photos](#)