



## Luminaire

# Burbu

19-205I-50GEE/830, S



In the Burbu family, we round off squares with corners and we make ovals from rectangles. These luminaires with a 70 mm profile height have a positive and pleasant effect in the room. Combine luminaires with different diameters and different hanging possibilities. In a range of colours and power versions, flush-mount, wall and pendant models, the Burbu family of luminaires are ideal for hotel lobbies, entrance halls, offices, shops and households.

## Technical drawing



|  |  |
|--|--|
| Type of installation                     | Surface, Wall mounted, Suspended         |
| Light distribution                       | Direct                                   |
| Luminaire shape                          | Rounded                                  |
| Colour of the luminaires                 | Silver                                   |
| Material                                 | Aluminium                                |
| Lifetime                                 | L80/B20 50 000 hours                     |
| Warranty                                 | 5 years                                  |
| Description of luminaires                | Luminaire surface/wall mounted/suspended |
| Dimensions                               | 1522 mm × 155 mm × 70 mm                 |
| Weight                                   | 6.9 kg                                   |
| Light source                             | LED MODUL                                |
| Type of optical system                   | Microprisma                              |
| Luminous flux*                           | 4110 lm                                  |
| Colour Temperature                       | 3000 K warm white                        |
| Luminous efficacy                        | 87 lm/W                                  |
| MacAdam Light source                     | 3  |
| Colour rendering index                   | 80                                       |
| UGR max. X=4H<br>Y=8H, $\theta=70,50,20$ | 18.8                                     |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 47 W     |
| Connection of the luminaires | ON/OFF   |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

 **CE** IP 20

\*±10 %

## Downloads

Installation instructions



Photos



## Accessories



**00-00333, S**  
suspension set  
2000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**19-0009, S**  
Mounting distance kit for square  
luminaire, circular 370 mm