



## Luminaire

# Burbu

19-214I-40GEM/830, B



In the Burbu family, we round off squares with corners and we make ovals from rectangles. These luminaires with a 70 mm profile height have a positive and pleasant effect in the room. Combine luminaires with different diameters and different hanging possibilities. In a range of colours and power versions, flush-mount, wall and pendant models, the Burbu family of luminaires are ideal for hotel lobbies, entrance halls, offices, shops and households.

## Technical drawing



|                           |  |
|---------------------------|--|
| Type of installation      | Surface, Wall mounted, Suspended         |
| Light distribution        | Direct                                   |
| Luminaire shape           | Rounded                                  |
| Colour of the luminaires  | Black                                    |
| Material                  | Aluminium                                |
| Lifetime                  | L80/B20 50 000 hours                     |
| Warranty                  | 5 years                                  |
| Description of luminaires | Luminaire surface/wall mounted/suspended |
| Dimensions                | 600 mm × 600 mm × 70 mm                  |
| Light source              | LED MODUL                                |

|                                   |                   |
|-----------------------------------|-------------------|
| Type of optical system            | Microprisma       |
| Luminous flux*                    | 3700 lm           |
| Colour Temperature                | 3000 K warm white |
| Luminous efficacy                 | 109 lm/W          |
| MacAdam Light source              | 3                 |
| Colour rendering index            | 80                |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 16.5              |

|                              |                       |
|------------------------------|-----------------------|
| Luminaire power input*       | 34.1 W                |
| Connection of the luminaires | ON/OFF + 1h emergency |
| Electrical voltage           | 220-240V              |
| Frequency                    | 50/60Hz               |

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos



## Accessories



**00-00333, B**  
suspension set  
2000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**00-00340, B**  
suspension set  
4000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**00-00344, B**  
suspension set  
6000mm, 4 pcs.of wires,  
cable 5x0,75mm, ceiling  
cup



**19-0009, B**  
Mounting distance kit for square  
luminaire, circular 370 mm