


**Luminaire**

# Rundo 62

190-241I-10GGD/840, S +  
00-00384-1000/RUN, S



Circular luminaires with an aluminium profile come in height 62 mm feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

|                                   |  |
|-----------------------------------|--|
| Type of installation              | Suspended                                |
| Light distribution                | Direct-indirect                          |
| Luminaire shape                   | Circular                                 |
| Colour of the luminaires          | Silver                                   |
| Material                          | Aluminium                                |
| Lifetime                          | L80/B10 50 000 hours                     |
| Warranty                          | 5 years                                  |
| Description of luminaires         | Luminaire suspended                      |
| item description                  | Silver ceiling cup and transparent cable |
| Dimensions                        | ø 400 mm × 62 mm                         |
| Light source                      | LED MODUL                                |
| DIR optical system                | Microprisma                              |
| INDIR optical system              | Opal cover                               |
| Luminous flux*                    | 3090 lm                                  |
| Colour Temperature                | 4000 K cool white                        |
| Luminous efficacy                 | 110 lm/W                                 |
| MacAdam Light source              | 3  |
| Colour rendering index            | 80                                       |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 16.3                                     |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 28 W     |
| Connection of the luminaires | DALI     |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

 **CE** IP 40

\*±10 %

## Downloads

Installation instructions



Photos

