



## Luminaire

# Rundo 62

190-241K-10GGMI/830, B



Circular luminaires with an aluminium profile come in height 62 mm feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

## Technical drawing



|   |   |
|---|---|
| Type of installation                      | Surface, Wall mounted                             |
| Light distribution                        | Direct-indirect                                   |
| Luminaire shape                           | Circular  |
| Colour of the luminaires                  | Black   |
| Material                                  | Aluminium   |
| Lifetime                                  | L80/B20 50 000 hours                              |
| Warranty                                  | 5 years   |
| Description of luminaires                 | Luminaire surface/wall mounted                    |
| Dimensions                                | $\varnothing 400 \text{ mm} \times 62 \text{ mm}$ |
| Weight                                    | 3.6 kg  |
| Light source                              | LED MODUL   |
| Type of optical system                    | Opal diffuser                                     |
| Luminous flux                             | 3500 lm $\pm 10 \%$                               |
| Colour Temperature                        | 3000 K warm white                                 |
| Luminous efficacy                         | 121 lm/W  |
| MacAdam Light source                      | 3   |
| Colour rendering index                    | 80  |
| UGR max. X=4H<br>Y=8H, $\varrho=70,50,20$ | 21.6  |

## Curve



Luminaire power input 28.9 W  $\pm$  10 %

Connection of the luminaires Electronic ballast non-dimmable, multiwatt with 1h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

