




**Luminaire**

# Rundo 62

**190-260I-10GGD/840, W**


Circular luminaires with an aluminium profile come in height 62 mm feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

**Technical drawing**


|   |                                     |
|---|-------------------------------------|
| Type of installation                      | Surface, Wall mounted               |
| Light distribution                        | Direct                              |
| Luminaire shape                           | Circular                            |
| Colour of the luminaires                  | White                               |
| Material                                  | Aluminium                           |
| Lifetime                                  | L90/B50 50 000 hours                |
| Warranty                                  | 5 years                             |
| Description of luminaires                 | Luminaire surface/wall mounted      |
| Dimensions                                | $\varnothing$ 600 mm $\times$ 62 mm |
| Weight                                    | 6.3 kg                              |
| Light source                              | LED MODUL                           |
| Type of optical system                    | Microprisma                         |
| Luminous flux                             | 4920 lm $\pm$ 10 %                  |
| Colour Temperature                        | 4000 K cool white                   |
| Luminous efficacy                         | 110 lm/W                            |
| MacAdam Light source                      | 3                                   |
| Colour rendering index                    | 80                                  |
| UGR max. X=4H<br>Y=8H, $\varrho=70,50,20$ | 18.5                                |

## Curve



Luminaire power input 44.7 W ± 10 %

Connection of the luminaires DALI dimmable

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE  IP 40

