



## Luminaire

# Rundo 62

190-261I-10GGM3I/840, S



Circular luminaires with an aluminium profile come in height 62 mm feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

## Technical drawing



|                                           |                                                   |
|-------------------------------------------|---------------------------------------------------|
| Type of installation                      | Surface, Wall mounted                             |
| Light distribution                        | Direct-indirect                                   |
| Luminaire shape                           | Circular                                          |
| Colour of the luminaires                  | Silver                                            |
| Material                                  | Aluminium                                         |
| Lifetime                                  | L80/B20 50 000 hours                              |
| Warranty                                  | 2 years                                           |
| Description of luminaires                 | Luminaire surface/wall mounted                    |
| Dimensions                                | $\varnothing 600 \text{ mm} \times 62 \text{ mm}$ |
| Weight                                    | 6.8 kg                                            |
| Light source                              | LED MODUL                                         |
| Type of optical system                    | Microprisma                                       |
| Luminous flux*                            | 4500 lm                                           |
| Colour Temperature                        | 4000 K cool white                                 |
| Luminous efficacy                         | 109 lm/W                                          |
| MacAdam Light source                      | 3                                                 |
| Colour rendering index                    | 80                                                |
| UGR max. X=4H<br>Y=8H, $\varrho=70,50,20$ | 16.4                                              |

## Curve



Luminaire power input\* 41.1 W

Connection of the luminaires ON/OFF + 3h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

\*±10 %

