



Luminaire

Rundo 62

190-281K-10GGM3/840, W



Circular luminaires with an aluminium profile come in height 62 mm feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

Technical drawing



| | |
|---------------------------|-------------------------------------|
| Type of installation | Surface, Wall mounted |
| Light distribution | Direct-indirect |
| Luminaire shape | Circular |
| Colour of the luminaires | White |
| Material | Aluminium |
| Lifetime | L80/B10 50 000 hours |
| Warranty | 5 years |
| Description of luminaires | Luminaire surface/wall mounted |
| Dimensions | \varnothing 850 mm \times 62 mm |
| Light source | LED MODUL |

| | |
|--|---------------------|
| Type of optical system | Opal diffuser |
| Luminous flux | 10940 lm \pm 10 % |
| Colour Temperature | 4000 K cool white |
| Luminous efficacy | 136 lm/W |
| MacAdam Light source | 3 |
| Colour rendering index | 80 |
| UGR max. X=4H Y=8H, $\rho=70,50,20$ | 21.9 |

Curve



Luminaire power input 80.7 W \pm 10 %

Connection of the luminaires Electronic ballast non-dimmable with 3h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

