



## Luminaire

# Rundo 62

190-281K-10GGM3I/830, W



Circular luminaires with an aluminium profile come in height 62 mm feature an excellent efficacy of up to 145 lm/W, which can give the space lightness and appeal. The luminaires are pendant or flush-mounted, with direct or direct-indirect distribution of light creating an interesting light halo. A circular luminaire with a PMMA opal diffuser or microprismatic optical system is suitable for both commercial spaces and households. A playful and interesting effect can be created by combining different diameters. Luminaires can be equipped with a motion sensor, daylight sensor or Bluetooth technology, which allows easy control of the luminaire from your smart device.

## Technical drawing



|  |                                     |
|--|-------------------------------------|
| Type of installation                   | Surface, Wall mounted               |
| Light distribution                     | Direct-indirect                     |
| Luminaire shape                        | Circular                            |
| Colour of the luminaires               | White                               |
| Material                               | Aluminium                           |
| Lifetime                               | L80/B10 50 000 hours                |
| Warranty                               | 5 years                             |
| Description of luminaires              | Luminaire surface/wall mounted      |
| Dimensions                             | $\varnothing$ 850 mm $\times$ 62 mm |
| Light source                           | LED MODUL                           |
| Type of optical system                 | Opal diffuser                       |
| Luminous flux*                         | 10500 lm - 10000 lm                 |
| Colour Temperature                     | 3000 K warm white                   |
| Luminous efficacy                      | 131 lm/W                            |
| MacAdam Light source                   | 3                                   |
| Colour rendering index                 | 80                                  |
| UGR max. X=4H<br>Y=8H, $\rho=70,50,20$ | 21.8                                |

## Curve



Luminaire power input\* 80.3 W

Connection of the luminaires ON/OFF + 3h emergency

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

\* $\pm 10\%$

