


Luminaire

Rundo 87


191-250I-10GED/840, B



Circular luminaires with an aluminium profile with a height of 87 mm and an excellent luminous efficacy of up to 145 lm/W. A Rundo87 family not only by its name, but also in terms of its functions and dimensions with a diameter of up to 1150 mm. These surface or pendant luminaires can be used as basic lighting features in commercial and residential spaces. Thanks to sophisticated technology, the luminaires do not cause glare and the lighting can be adapted to smaller or large commercial spaces. You can choose between a version with an opal diffuser made of PMMA or a microprismatic optical system.

Type of installation	Surface, Wall mounted
Light distribution	Direct
Luminaire shape	Circular
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L90/B50 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire surface/wall mounted
Dimensions	ø 500 mm × 87 mm
Weight	5.8 kg
Light source	LED MODUL
DIR optical system	Microprisma
Luminous flux*	3210 lm
Colour Temperature	4000 K cool white
Luminous efficacy	107 lm/W
MacAdam Light source	3
Colour rendering index	80
UGR max. X=4H Y=8H, ρ=70,50,20	18.3

Technical drawing



Luminaire power input* 29.9 W

Connection of the luminaires DALI


Electrical voltage 220-240V

Frequency 50/60Hz

   IP 40

* $\pm 10\%$

Curve



Downloads

Installation instructions



Photos

