


**Luminaire**

# Rundo 87

191-260I-10GGQ/TC, W



Circular luminaires with an aluminium profile with a height of 87 mm and an excellent luminous efficacy of up to 145 lm/W. A Huge family not only by its name, but also in terms of its functions and dimensions with a diameter of up to 1150 mm. These surface or pendant luminaires can be used as basic lighting features in commercial and residential spaces. Thanks to sophisticated technology, the luminaires do not cause glare and the lighting can be adapted to smaller or large commercial spaces. You can choose between a version with an opal diffuser made of PMMA or a microprismatic optical system.

**Technical drawing**


|                           |                                |
|---------------------------|--------------------------------|
| Type of installation      | Surface, Wall mounted          |
| Light distribution        | Direct                         |
| Luminaire shape           | Circular                       |
| Colour of the luminaires  | White                          |
| Material                  | Aluminium                      |
| Lifetime                  | L80/B20 50 000 hours           |
| Warranty                  | 5 years                        |
| Description of luminaires | Luminaire surface/wall mounted |
| Dimensions                | ø 600 mm × 87 mm               |
| Light source              | LED MODUL                      |

|                                   |                               |
|-----------------------------------|-------------------------------|
| Type of optical system            | Microprisma                   |
| Luminous flux                     | 3780 lm ± 10 %                |
| Colour Temperature                | 2700 K - 6500 K Tunable White |
| Luminous efficacy                 | 78 lm/W                       |
| MacAdam Light source              | 3                             |
| Colour rendering index            | 90                            |
| UGR max. X=4H<br>Y=8H, ρ=70,50,20 | 17.5                          |

## Curve



Luminaire power input 48.3 W  $\pm$  10 %

Connection of the luminaires DALI DT8

Electrical voltage 220-240V

Frequency 50/60Hz

⊕ CE IP 40

## Downloads

Installation instructions



Photos

