



## Luminaire

# Rundo 87

191-280K-10GGQ/TC, W



Circular luminaires with an aluminium profile with a height of 87 mm and an excellent luminous efficacy of up to 145 lm/W. A Huge family not only by its name, but also in terms of its functions and dimensions with a diameter of up to 1150 mm. These surface or pendant luminaires can be used as basic lighting features in commercial and residential spaces. Thanks to sophisticated technology, the luminaires do not cause glare and the lighting can be adapted to smaller or large commercial spaces. You can choose between a version with an opal diffuser made of PMMA or a microprismatic optical system.

Type of installation	Surface, Wall mounted
Light distribution	Direct
Luminaire shape	Circular
Colour of the luminaires	White
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire surface/wall mounted
Dimensions	ø 850 mm × 87 mm
Weight	13.8 kg
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux	8510 lm ± 10 %
Colour Temperature	2700 K - 6500 K Tunable White
Luminous efficacy	99 lm/W
MacAdam Light source	3
Colour rendering index	90
Luminaire power input	86 W ± 10 %
Connection of the luminaires	DALI DT8
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 40

## Downloads

Installation instructions



Photos

