



## Luminaire

# Rotao60

227-5D1K-10GGE/840, B



The designer circular luminaire Rotao60 comes in a large number of diameters, thanks to which it fits well into various social and commercial spaces. You can also use it to decorate your living room or a meeting room. If you combine the luminaire with microprismatic optics, its efficacy can be surprising even in an office. Pendant versions of the Rotao60 luminaire with a diameter of up to 800 mm are suspended on suspension wires which converge into a single ceiling cup, while larger diameters are suspended on wires that run perpendicular to the ceiling.

## Technical drawing



|                           |                      |
|---------------------------|----------------------|
| Type of installation      | Suspended            |
| Light distribution        | Direct-indirect      |
| Luminaire shape           | Circular             |
| Colour of the luminaires  | Black                |
| Material                  | Aluminium            |
| Lifetime                  | L80/B20 50 000 hours |
| Warranty                  | 5 years              |
| Description of luminaires | Luminaire suspended  |
| Dimensions                | ∅ 2050 mm × 65 mm    |
| Weight                    | 13.3 kg              |
| Light source              | LED MODUL            |
| Type of optical system    | Opal diffuser        |
| Luminous flux*            | 14780 lm             |
| Colour Temperature        | 4000 K cool white    |
| Luminous efficacy         | 100 lm/W             |
| MacAdam Light source      | 3                    |
| Colour rendering index    | 80                   |

Luminaire power input\* 148.3 W

---

Connection of the luminaires ON/OFF

---

Electrical voltage 220-240V

---

Frequency 50/60Hz

---

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos

