


**Luminaire**

# Flumo60-S

**228S-501I-15GEE/830, B**


Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

|                              |                            |
|------------------------------|----------------------------|
| Type of installation         | Suspended                  |
| Light distribution           | Direct-indirect            |
| Luminaire shape              | Linear                     |
| Colour of the luminaires     | Black                      |
| Material                     | Aluminium                  |
| Lifetime                     | L80/B20 50 000 hours       |
| Warranty                     | 5 years                    |
| Description of luminaires    | Luminaire suspended        |
| Dimensions                   | 860 mm × 60 mm × 65 mm     |
| Light source                 | LED MODUL                  |
| Type of optical system       | Microprisma, Opal diffuser |
| Luminous flux*               | 1030 lm                    |
| Colour Temperature           | 3000 K warm white          |
| Luminous efficacy            | 72 lm/W                    |
| MacAdam Light source         | 3                          |
| Colour rendering index       | 80                         |
| Luminaire power input*       | 14.3 W                     |
| Connection of the luminaires | ON/OFF                     |
| Electrical voltage           | 220-240V                   |
| Frequency                    | 50/60Hz                    |


**CE IP 20**

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories****00-00300, N**  
wire suspension  
2000mm**00-00301, N**  
wire suspension  
4000mm**00-00302, N**  
wire suspension  
6000mm**00-00352, K**  
cable 3x0,75 2000mm**00-00358, K**  
cable 3x0,75 4000mm**00-00360, K**  
cable 3x0,75 6000mm**00-00370, B**  
ceiling cup 80x80x32mm**228-20101, B**  
2 end caps**228-20200, N**  
arranging coupler