


Luminaire

Flumo60-S

228S-501I-25GGD/830, S


Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation	Suspended
Light distribution	Direct-indirect
Luminaire shape	Linear
Colour of the luminaires	Silver
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
Dimensions	1420 mm × 60 mm × 65 mm
Light source	LED MODUL
Type of optical system	Microprisma, Opal diffuser
Luminous flux*	2700 lm
Colour Temperature	3000 K warm white
Luminous efficacy	79 lm/W
MacAdam Light source	3
Colour rendering index	80
Luminaire power input*	34.2 W
Connection of the luminaires	DALI
Electrical voltage	220-240V
Frequency	50/60Hz


CE IP 20

*±10 %

Downloads

Installation instructions



Photos



Accessories**00-00300, N**
wire suspension
2000mm**00-00301, N**
wire suspension
4000mm**00-00302, N**
wire suspension
6000mm**00-00356, K**
cable 5x0,75 4000mm**00-00357, K**
cable 5x0,75 6000mm**00-00363, K**
cable 5x1,5 2000mm**00-00370, S**
ceiling cup 80x80x32mm**228-20101, S**
2 end caps**228-20200, N**
arranging coupler