


Luminaire

Flumo60-S

228S-501I-30GGE/840, B


Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation	Suspended
Light distribution	Direct-indirect
Luminaire shape	Linear
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
Dimensions (l × w × h mm)	1700 mm × 60 mm × 65 mm
Light source	LED MODUL
DIR optical system	Microprisma
INDIR optical system	Opal cover
Luminous flux*	2980 lm
Colour Temperature	4000 K cool white
Luminous efficacy	75 lm/W
MacAdam Light source	3
Colour rendering index	80

Luminaire power input*	39.7 W
Connection of the luminaires	ON/OFF
Electrical voltage	220-240V
Frequency	50/60Hz

 **CE** IP 20

*±10 %

Downloads

Installation instructions



Photos



Accessories**00-00300, N**
wire suspension
2000mm**00-00301, N**
wire suspension
4000mm**00-00302, N**
wire suspension
6000mm**00-00352, B**
cable 3x0,75 2000mm,
black**00-00358, B**
cable 3x0,75 4000mm,
black**00-00360, B**
cable 3x0,75 6000mm,
black**00-00370, B**
ceiling cup 80x80x32mm**228-20101, B**
2 end caps**228-20200, N**
arranging coupler