


**Luminaire**

# Flumo60-S

**228S-501I-40GED/840, W**


Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

|                              |                         |
|------------------------------|-------------------------|
| Type of installation         | Suspended               |
| Light distribution           | Direct-indirect         |
| Luminaire shape              | Linear                  |
| Colour of the luminaires     | White                   |
| Material                     | Aluminium               |
| Lifetime                     | L80/B20 50 000 hours    |
| Warranty                     | 5 years                 |
| Description of luminaires    | Luminaire suspended     |
| Dimensions<br>(l × w × h mm) | 2260 mm × 60 mm × 65 mm |
| Light source                 | LED MODUL               |
| DIR optical system           | Microprisma             |
| INDIR optical system         | Opal cover              |
| Luminous flux*               | 3790 lm                 |
| Colour Temperature           | 4000 K cool white       |
| Luminous efficacy            | 92 lm/W                 |
| MacAdam Light source         | 3                       |
| Colour rendering index       | 80                      |

|                              |          |
|------------------------------|----------|
| Luminaire power input*       | 41.4 W   |
| Connection of the luminaires | DALI     |
| Electrical voltage           | 220-240V |
| Frequency                    | 50/60Hz  |

 **CE** IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**


**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm



**00-00302, N**  
wire suspension  
6000mm



**00-00356, W**  
cable 5x0,75 4000mm,  
white



**00-00357, W**  
cable 5x0,75 6000mm,  
white



**00-00363, K**  
cable 5x1,5 2000mm



**00-00370, W**  
ceiling cup 80x80x32mm



**228-20101, W**  
2 end caps



**228-20200, N**  
arranging coupler