



## Luminaire

# Flumo60-S

228S-501I-40GGQ/TC, B



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

|                              |                               |
|------------------------------|-------------------------------|
| Type of installation         | Suspended                     |
| Light distribution           | Direct-indirect               |
| Luminaire shape              | Linear                        |
| Colour of the luminaires     | Black                         |
| Material                     | Aluminium                     |
| Lifetime                     | L80/B20 50 000 hours          |
| Warranty                     | 5 years                       |
| Description of luminaires    | Luminaire suspended           |
| Dimensions                   | 2260 mm × 60 mm × 65 mm       |
| Type of optical system       | Microprisma, Opal diffuser    |
| Luminous flux*               | 3450 lm                       |
| Colour Temperature           | 2700 K - 6500 K Tunable White |
| MacAdam Light source         | 3                             |
| Colour rendering index       | 90                            |
| Connection of the luminaires | DALI DT8                      |
| Electrical voltage           | 220-240V                      |
| Frequency                    | 50/60Hz                       |

 **CE** IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories****00-00300, N**  
wire suspension  
2000mm**00-00301, N**  
wire suspension  
4000mm**00-00302, N**  
wire suspension  
6000mm**00-00356, K**  
cable 5x0,75 4000mm**00-00357, K**  
cable 5x0,75 6000mm**00-00363, K**  
cable 5x1,5 2000mm**00-00370, B**  
ceiling cup 80x80x32mm**228-20101, B**  
2 end caps**228-20200, N**  
arranging coupler