


**Luminaire**

# Flumo60-S

**228S-560K-060ED/840, B**


Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation	Suspended
Light distribution	Direct
Luminaire shape	Rounded
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
item description	Arch R302 - 60°
Dimensions	316 mm × 60 mm × 65 mm
Light source	LED MODUL
Type of optical system	Opal diffuser
Luminous flux*	370 lm
Colour Temperature	4000 K cool white
Luminous efficacy	95 lm/W
MacAdam Light source	3
Colour rendering index	80

Luminaire power input*	3.9 W
Connection of the luminaires	DALI
Electrical voltage	220-240V
Frequency	50/60Hz

 **CE** IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories****00-00300, N**  
wire suspension  
2000mm**00-00301, N**  
wire suspension  
4000mm**00-00302, N**  
wire suspension  
6000mm**00-00356, K**  
cable 5x0,75 4000mm**00-00357, K**  
cable 5x0,75 6000mm**00-00363, K**  
cable 5x1,5 2000mm**00-00370, B**  
ceiling cup 80x80x32mm**228-20101, B**  
2 end caps**228-20200, N**  
arranging coupler