



Luminaire

Flumo60-S

228S-560K-090ED/830, B



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation Suspended

Light distribution Direct

Luminaire shape Rounded

Colour of the luminaires Black

Material Aluminium

Lifetime L80/B20 50 000 hours

Warranty 5 years

Description of luminaires Luminaire suspended

item description Arch R302 - 90°

Dimensions (w × h mm) 60 mm × 65 mm

Diameter ø 302

Angle 90 °

Light source LED MODUL

DIR optical system Opal diffuser

Luminous flux* 530 lm

Colour Temperature 3000 K warm white

Luminous efficacy 90 lm/W

MacAdam Light source 3

Colour rendering index 80

Luminaire power input*	5.9 W
Connection of the luminaires	DALI
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 20

*±10 %

Downloads

[Installation instructions](#)[Photos](#)

Accessories



00-00300, N
wire suspension
2000mm




00-00301, N
wire suspension
4000mm




00-00302, N
wire suspension
6000mm



00-00356, K
cable 5x0,75 4000mm,
transparent



00-00357, K
cable 5x0,75 6000mm,
transparent



00-00363, K
cable 5x1,5 2000mm



00-00370, B
ceiling cup 80x80x32mm



228-20101, B
2 end caps



228-20200, N
arranging coupler