



## Luminaire

# Flumo60-S

228S-561I-135EE/840, B



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation	Suspended
Light distribution	Direct-indirect
Luminaire shape	Rounded
Colour of the luminaires	Black
Material	Aluminium
Lifetime	L80/B20 50 000 hours
Warranty	5 years
Description of luminaires	Luminaire suspended
item description	Arch R302 - 135°
Dimensions	711 mm × 60 mm × 65 mm
Light source	LED MODUL
Type of optical system	Microprisma, Opal diffuser
Luminous flux*	870 lm
Colour Temperature	4000 K cool white
Luminous efficacy	80 lm/W
MacAdam Light source	3
Colour rendering index	80

Luminaire power input*	10.9 W
Connection of the luminaires	ON/OFF
Electrical voltage	220-240V
Frequency	50/60Hz

  IP 20

\*±10 %

## Downloads

Installation instructions



Photos



**Accessories**


**00-00300, N**  
wire suspension  
2000mm



**00-00301, N**  
wire suspension  
4000mm



**00-00302, N**  
wire suspension  
6000mm



**00-00352, K**  
cable 3x0,75 2000mm



**00-00358, K**  
cable 3x0,75 4000mm



**00-00360, K**  
cable 3x0,75 6000mm



**00-00370, B**  
ceiling cup 80x80x32mm



**228-20101, B**  
2 end caps



**228-20200, N**  
arranging coupler